



CCTV Camera DVR System



PC Base DVR

[KRS-1104 / 2209 / 4116 / 4216]

- Various Product Line-up to Meet Market Needs
 - PC Base DVR : 4 Models (KRS-1104, KRS-2209, KRS-4116, KRS-4216)
- Best Surveillance & Recording Performance
 - Display : Max. 480fps
 - Recording : Max. 240fps
- Powerful Networking Support
 - Remote Surveillance, Search, P/T/Z Control & Setup
 - CTMS(Central Monitoring & Management System)
- Multiple Image Resolution
 - Variable Image Resolution per Camera according to the Importance of Surveillance Object
- Simultaneous Recording of Video & Audio
- Audio Detection
- Automatic Warning in Emergency
- Smart search & Mapping Search
- Panorama Search & Detail Search
- Water Marking for Image Forgery
- Pre & Post Recording by Alarm
- System Protection by Password
- Quick & Easy System Setup
- Compatibility with Analog System
- Various Operating System - Windows 2000

Specifications

Model no.	KRS-4216	KRS-4116	KRS-2209	KRS-1104
Max. Display Speed	480 frame/sec	480 frame/sec	270 frame/sec	120 frame/sec
Max. Recording Speed	240 frame/sec	120 frame/sec	270 frame/sec	120 frame/sec
Resolution	320X240, 640X480 Variable			
File Size	2 ~ 15 Kbytes / frame			
Compression	MJPEG Enhanced MJPEG			
Split Screen Mode	"1, 4, 9, 16" "1+5, 1+7, 1+9, 1+12, 1+16"	"1, 4, 9, 16" "1+5, 1+7, 1+9, 1+12, 1+16"	"1, 4, 9" "1+5, 1+7, 1+9"	"1, 4" "1+5"
Remote Control	LAN, ISDN, TCP/IP, ADSL			
Camera Input	16 CH	16 CH	9 CH	4 CH
Audio Input	8 CH	4 CH	8 CH	4 CH
Sensor In / Digital Out	8 CH	8 CH	8 CH	8 CH
Monitor output	PC monitor : 1port Analog monitor : 2 port	PC monitor : 1port Analog monitor : 2 port	PC monitor : 1port Analog monitor : 1 port	PC monitor : 1port Analog monitor : 1 port
Recording mode	Continuous, Motion, Sensor, Audio Detection, Pre & Post-Alarm(Event),Schedule(Camera/Date/Time)			
HDD Storage	80GB (default) Up to 250GB HDD is available optional / Max. 8 HDDs (Max. 2 TB)			
OS / System	Window 2000 / Pentium IV-2.0 GHz CPU, 256SDRAM (512SDRAM, option)			
Software	Client, Backup Viewer, Watermark Viewer, CTMS (option)			
Backup device / file	3.5" FDD, USB, DVD-RW, CD-RW(Optional) / DVR file(with Backup Viewer Software), JPG, BMP, AVI			
Dimension	432 x 457 x 178 (WxDxH,mm)			
Pan / Tilt	RS485			

• The product may include option or additional functions.